




Parameters and available chair sizes

Size	Seat height	Body height
3 - 5	350 - 430 mm	119 - 176,5 cm
5 - 7	430 - 510 mm	146 - 207 cm

Dimensions:	The overall dimensions and weight of the product vary according to size.
Carrying capacity:	MAX. 120 KG.
Stackability:	Yes
Note:	The specified size is (± 10 mm) according to EN 1729 - 1.

- Designed 'S FORM' chair frame
- Almost indestructible steel construction
- Height adjustable with tools
- Natural beech plywood
- Scratch resistant
- Customizable colors and components
- Stackable



Standard chair design

Steel
RAL 9006
Beech plywood
Natural, varnished
Without felt

You can view or download the color and accessory adjustment sheets from our website.

Detailed description

The popular Z31 school chair is designed with a modern 'S FORM' metal base. The chair's construction is almost indestructible. It is made of 38x20 mm flat-oval steel profiles with 1.5 mm wall thickness, ensuring its high strength and durability. The metal structure is powder-coated in the timeless RAL 9006 (white aluminium). The chair can be adjusted in height using tools.

The seat and backrest are 8mm thick molded beech plywood with a clear lacquer finish. This surface is highly scratch-resistant, extending the chair's life even in everyday use.

The Z31 chair has plastic glides as standard to protect the floor and ensure stability. The glides are available without felt, but this component can be replaced with a felt version on request.

The chair is low maintenance and easy to clean, making it an ideal choice for school environments.

The product offers individual customization options such as changing the frame, seat, and backrest color. Swatches of colors and other finishes are available to tailor the chair to specific requirements.

Maintenance

The metal and beech plywood surfaces can be maintained with common cleaning agents, with the exception of aggressive cleaners, detergents, polishes, and products containing granules and sand. Do not expose the chair to excessive moisture or running water or to temperatures above 90 °C.