DL20V

Two-Person Student Desk, Height-Adjustable

- **Simple and functional design**
- **Adjustable in height with tools**
- **Practical hooks for school backpacks**
- **Rigid steel construction made of flat oval profiles**
- **Component configuration options**
- **Large selection of finishes and colors**



Parameters and available sizes

Size	Worktop height	Body height
3 - 5	590 - 710 mm	119 - 176,5 cm
5 - 7	710 - 820 mm	146 - 207 cm

Dimensions:	The overall dimensions and weight of the product vary according to size.
Carrying capacity:	MAX. 120 KG.
Stackability:	No
Note:	The specified size is (± 10 mm) according to EN 1729 - 1.

Standard desk design

Frame material:	Steel
Frame color:	RAL 9006
Worktop dimensions:	130x50cm
Type of worktop:	TYPE A (THK.18mm, sharp corner, 2mm ABS edge)
Worktop material:	Laminated chipboard
Worktop finish:	Beech, white
Glides:	Without felt

You can view or download the color and accessory adjustment sheets from our website.

Digital and/or printed color reproduction may vary from the actual color. Colors are subject to change.

Detailed description

The simple and functional design of the DL20V desk is perfect for a school environment.

The welded frame of the desk is made of flat-oval steel profiles, which guarantee high durability and stability. It is treated with powder coating in RAL 9006 (white aluminum). The desk's frame allows height adjustment using tools. It also includes practical hooks for hanging school backpacks. The glides are without felt. This component can be replaced with a felt variant.

The desk has a worktop, TYPE A, made of 18-mm-thick laminated chipboard with a 2-mm ABS edge and sharp corners, measuring 130x50cm. The worktop is standard in white or beech finish, but it can be configured in type and finish according to demand.

The desk is easy to maintain and easy to clean.

Maintenance

The metal surface and the worktop surface can be maintained with common cleaning agents, except aggressive cleaners, detergents, polishes, and products containing granules and sand. Do not expose the product to excessive moisture, running water, or temperatures above 90 °C.