



Parameters and available sizes

Size	Worktop height	Body height
3 - 5	590 - 710 mm	119 - 176,5 cm
5 - 7	710 - 820 mm	146 - 207 cm

Dimensions: The overall dimensions and weight

of the product vary according to size.

MAX. 120 KG. Carrying capacity:

Stackability: No

Note: The specified size is $(\pm 10 \text{ mm})$

according to EN 1729 - 1.

- Minimalist design
- Height adjustable without tools with screw locking option
- Practical hooks for school backpacks
- Rigid construction made of flat oval steel profiles 50x30 mm
- **Configuration options of components**
- Option to change the finish of the board and the color of the metal frame





Standard desk design

Frame material:	Steel
Frame color:	RAL 9006
Worktop dimensions:	130x50cm
Type of worktop:	TYPE A

(THK.18mm, sharp corner,

2mm ABS edge)

Worktop material: Laminated chipboard

Worktop finish: Beech, white Glides: Without felt

You can view or download the color and accessory adjustment sheets from our website.

Detailed description

The minimalist design of the DL40V desk helps create a modern and functional space in educational institutions. The desk allows height adjustment without the need for tools in the 3-5 or 5-7 version. The adjustment system is equipped with a screw, which with the usage of tools, can be used to block manual adjustment.

The frame is made of 50x30mm flat-oval steel profiles and is powder-coated in a neutral shade of RAL 9006 (white aluminum). It also includes practical hooks for hanging school backpacks. The glides are without felt. This component can be replaced with a felt variant.

The desk has a worktop, TYPE A, made of 18-mm-thick laminated chipboard with a 2-mm ABS edge and sharp corners, measuring 130x50cm. The worktop is standard in white or beech finish, but it can be configured in type and finish according to demand.

The desk is low maintenance and easy to clean.

Maintenance

The metal surface and the worktop surface can be maintained with common cleaning agents, except aggressive cleaners, detergents, polishes, and products containing granules and sand. Do not expose the product to excessive moisture, running water, or temperatures above 90 °C.