




Parameters and available sizes

Size	Worktop height	Body height	
3 - 7	590 - 820 mm	119 - 207 cm	
Dimensions:		The overall dimensions and weight of the product vary according to size.	
Carrying capac	city: MAX. 120 KG.	MAX. 120 KG.	
Stackability:	No		
Note:		The specified size is (± 10 mm) according to EN 1729 - 1.	

- Modern design
- Allows students to sit facing each other
- Drawer for school supplies
- Height adjustment in the range of height sizes 3 to 7
- Rigid welded construction
- Rounded corners of the worktop for increased safety
- Low maintenance



Standard desk design

Frame material:	Steel
Frame color:	RAL 9006
Worktop dimensions:	70x50cm
Worktop material:	Laminated chipboard
Worktop finish:	Beech, white
Glides:	Without felt
Drawer material:	Polypropylene
Drawer color:	Green

You can view or download the color and accessory adjustment sheets from our website.

Detailed description

The JL61V EDU student table offers a modern and functional design suitable for educational institutions, especially specialized classrooms. Its open structure allows students to sit facing each other, thus facilitating cooperation.

Tools are necessary for height adjustment in the range of height sizes 3 to 7.

The table's metal frame is welded from 40 mm diameter steel tubes and 40x20 mm steel profiles. The entire structure is standardly treated with powder coating in a neutral shade of RAL 9006 (white aluminium). Individual legs are equipped with rectifying glides to compensate for the floor's unevenness.

The table's worktop measures 70x50 cm and is made of 18mm thick laminated chipboard with a 2mm ABS edge. It also has R80 rounded corners for increased safety.

The storage space for school supplies is provided by a Gratnells plastic drawer made of polypropylene, which is offered in several colors.

The desk is easy to maintain and easy to clean.

Maintenance

The metal surface and the worktop surface can be maintained with common cleaning agents, except aggressive cleaners, detergents, polishes, and products containing granules and sand. Do not expose the product to excessive moisture, running water, or temperatures above 90 °C.